

# Hip & Ridge units – Shingle

## Technical specification

<b>Colour</b>	Natural, varying reddish brown to pale yellow
<b>Grade</b>	Blue Label, 100% Heartwood, 100% Edge Grain and 100% Clear
<b>Size</b>	450mm long, mitred right and left hand units, 2 widths 125mm (standard) & 190mm (extra wide, ideal for use with ridge vent system)
<b>Thickness</b>	10mm at the butt, tapering
<b>Profile</b>	Sawn both sides, rectangular
<b>Bundle</b>	36 pieces, 18 LH & 18 RH
<b>Min. pitch</b>	14°-30°*
<b>Min. side lap</b>	n/a

\*For roof pitches above 30°, hips and ridges must be site-formed using standard shingles. Contact TAS for further guidance

Max. gauge		Laid weight kg m <sup>2</sup> clean / treated / FRT
22-75°	125mm	4.5 6.1
14-21°	95mm	3.4 8.1

Weight	Per bundle	Per pallet (24 bundles)
Clean	14kg	336kg
Treated	28kg	672kg
FRT	16kg	382kg

Nail size	
Stainless steel ringshank nail	45 x 2.65mm

Performance	
Clean (Roofing)	Expected life 20-40 years dependent on use and aspect
Clean (Cladding)	Expected life 40-60 years
Treated (Roofing)	Guaranteed 40 years* to BS 8417 Expected life 40-60 years
Treated (Cladding)	Guaranteed 40 years* to BS 8417 Expected life 40-60 years
FRT (Roofing)	Expected life 40 years
FRT (Cladding)	Expected life 40-60 years

Fire	
Clean	n/a
Treated	C/B to BS476 pt 3
FRT (Cladding)	BS EN 13501-1 Euroclass B or C
FRT (Roofing)	AA/P60 To BS476 pt 3

\* See terms & conditions

Call 01427 613858  
Email [info@marleyeternit.co.uk](mailto:info@marleyeternit.co.uk)  
Or visit [www.marleyeternit.co.uk](http://www.marleyeternit.co.uk)



Marley Eternit Lichfield Road Branston Burton upon Trent DE14 3HD

an etex company