

600mm handsplit and resawn shakes

Technical specification

Colour	Natural, varying reddish brown to pale yellow
Grade	Blue Label, 100% Heartwood, 100% Edge Grain and 100% Clear
Size	600mm long, random widths 75mm-300mm
Thickness	19mm at the butt, tapering
Profile	Hand split face, sawn back, rectangular
Bundle	Approx. 44 pieces
Max. pitch	90°
Min. pitch	20°
Min. side lap	38mm

Max. gauge		Coverage m ² per bundle	Laid weight kg m ² clean / treated / FRT	Battens per m ²
75-90°	290mm	2.12	6.1 / 9.5 / 7.1	3.5m
20-74°	190mm [†]	1.39	9.4 / 14.4 / 10.8	5.3m

Min. batten size (JB Red battens)	
90°	25 x 50mm
450mm centres	25 x 38mm
600mm centres	25 x 38mm

Weight	Per bundle	Per pallet (20 bundles)
Clean	13kg	260kg
Treated	20kg	400kg
FRT	15kg	300kg

Nail size	
Stainless steel ringshank nail	45 x 2.65mm

Performance	
Clean (Roofing)	Expected life 20-40 years dependent on use and aspect
Clean (Cladding)	Expected life 40-60 years
Treated (Roofing)	Guaranteed 40 years* to BS 8417 Expected life 40-60 years
Treated (Cladding)	Guaranteed 40 years* to BS 8417 Expected life 40-60 years
FRT (Roofing)	Expected life 40 years
FRT (Cladding)	Expected life 40-60 years

Fire	
Clean	n/a
Treated	C/B to BS476 pt 3
FRT (Cladding)	BS EN 13501-1 Euroclass B or C
FRT (Roofing)	AA/P60 To BS476 pt 3

* See terms & conditions

† Maximum gauge 190mm if using a 3 ply construction with no interleaving or felt baffle

‡ Must use felt interleaving or felt baffle in between each course

Call 01427 613858
Email info@marleyeternit.co.uk
Or visit www.marleyeternit.co.uk



Marley Eternit Lichfield Road Branston Burton upon Trent DE14 3HD

an etex company